


# Cebú High Tensile Barbed Wire



High carbon barbed wires twisted together, which have a series of barbs placed on the wires every 5 inches.



## USES

- Perimeter fences of all kinds
- Security complement for fences made of mesh and concrete walls

## CHARACTERISTICS

- Spacing between barbs 5 in.
- Ergonomic handle
- High-strength wires

## ADVANTAGES

- Easy installation
- Saving on posts from wider spacing
- Excellent adaptability to different terrains
- Prestressed wires

## CEBÚ BARBED WIRE

Code	Wire Gauge		Length	Spacing between barbs	Number of rolls per pallet	Coating
	Length	Barbs				
			m	inch	units	Galvanized
59794	16	16.5	300	5	64	Commercial Grade
59798	16	16.5	360	5	64	Commercial Grade

## WIRE SPECIFICATIONS

Minimum breaking strength 350 kgf

For more information about Barbed Wire in USA, visit [www.rangemasterfence.com](http://www.rangemasterfence.com) and/or [www.staytuff.com](http://www.staytuff.com)

MANUFACTURING STANDARDS ASTM A-121 | ASTM A-641 | NMX-B-518



800 831 5700 | [ventas@deacero.com](mailto:ventas@deacero.com) | [deacero.com](http://deacero.com)

